



# GREASE-A-WAY

## CONCENTRATED CLEANER AND DEGREASER

### DESCRIPTION

GREASE-A-WAY is a super-concentrated cleaner/degreaser designed for use on concrete, brick, and masonry surfaces to dissolve dirt, dust, oil, and grease.

### PRIMARY APPLICATIONS

GREASE-A-WAY is recommended for surface preparation whenever degreasing is necessary prior to the application of overlays or sealers. It also can be used as a general purpose cleaner on concrete, overlay systems, terrazzo, marble, quarry tile, and stone floors.

### FEATURES/BENEFITS

GREASE-A-WAY is an economical means to clean up stains and blemishes from concrete, stone, and masonry surfaces. It is easy to use and can be adjusted in strength to provide the cleansing power needed for a variety of soils. Application strength can be adjusted according to use.

### TECHNICAL INFORMATION

Highly concentrated. One gal (3.8 L) of concentrate makes up to 20 gal (76 L) of usable product when diluted with water. At full strength GREASE-A-WAY can be used to strip wax.

### PACKAGING

GREASE-A-WAY is packaged in 1 gal (3.8 L) and 5 gal (18.9 L) units.

### SHELF LIFE

4 Years in original, unopened container

### DIRECTIONS FOR USE

For maintenance cleaning, mix 20 parts water to 1 part GREASE-A-WAY. Spray or wipe on, being sure to cover entire area. Rinse with water and dry. For concrete surface preparation, use 4 to 8 fl oz (118 to 236 mL) of GREASE-A-WAY degreaser to 1 gal (3.8 L) of water. Apply with a sprayer and agitate with a stiff broom. Allow to stand for 10 minutes then flush with clean water. For tough stains, apply GREASE-A-WAY uncut, and allow to stand for one hour before flushing away with clean water. Repeat if necessary.

Use GREASE-A-WAY undiluted as a stripper for waxes. Apply with a pump sprayer, brush vigorously and let stand for 5 to 10 minutes making sure the product does not dry. Remove by flushing with water.

### PRECAUTIONS/LIMITATIONS

- For professional use only.
- In all cases, consult the Safety Data Sheet before use.

Rev. 08.15

**WARRANTY:** The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.